

inalking o

# SLIM and DURABLE



# Ergonomically best possible g

achieved by the ingenious design of motor housing, rear cover and side grip:

Slim motor housing with a small circumference of 179mm

179mm

- Motor housing and rear cover ergonomically and uniquely ribbed for sure and comfortable gripping
- 3 Rear cover ergonomically tapered for easy gripping

Ergonomic 20° side grip angle



The angle of side grip to gear housing has been increased from conventional 10° for easier handling.

Anti-vibration grip (Optional accessory)



Small gear housing


Angle grinder GA4030 100mm (4")

GA4530 115mm (4-1/2")

GA5030 125mm (5")

Very comforta any gripping





## ripping


ble in

way

Extra-high reliability and durability

1) High quality motor with excellent

- 1) High quality motor with excellent heat-resistance
- 2 Reliable machined bevel gears



- Dust-proof ball bearings
- Motor field coated with protective powder varnish
- Two Labyrinth rings seal the ball bearings and entirely protect the gears and the motor from dust and dirt.







Powder varnish



Labyrinth ringFlat washerBearing box



Labyrinth rubber ring



Slide switch conveniently located for one hand operation

Toolless wheel cover



Powerful 720 W

### **Optional Accessories**





Part No.			
For Model GA4030			
135238-9			
-			
For Model GA4530			
135245-2			
135247-8			
	135238-9 - 135245-2		


For Model GA5030				
-	135240-2			
Toolless	135242-8			



For Model	Part No.	
GA5030	135270-3	




For Model	Part No.	
GA4030	192454-6	
GA5030	193066-8	





А	B		
Туре	Part No.		
For Model GA4030			
А	192475-8		
For Model GA4530, GA5030			
А	192618-2		
B (W/O Joint)	192972-4		
B (W/ Joint)	192968-5		
B (W/ Joint)	*193794-5		

Grip	Thakit	a
Stick	Anti Vibration Grip (Vibration Proof Grip)	
Туре	Part No.	
Stick (short type)	153504-2	
Stick	153489-2	
Anti Vibration Grip	194514-0	



Ì				
	Outer dia.(mm)	Type	Part No.	
	For Model GA4030			
	76	-	743009-6	
	For Model GA4530			
	100	Α	794187-5	
	100	В	743036-3	
	For Model GA5030			
	115	-	743015-1	

B: For spindle thread M16 x 2



### **Angle Grinder** GA4030 100mm (4")/ GA4530 115mm (4-1/2")/ GA5030 125mm (5") **Double Insulation** GA4030 **Continuous rating Input** 720W 720W 720W **Capacity** Depressed center wheel: 100mm (4") 115mm (4-1/2") 125mm (5") No load speed (rpm) 11,000 11,000 11,000 266x 117 x 95mm (10-1/2" x 4-5/8" x 3-3/4") 1.7kg (3.7lbs) 266 x 128 x 103mm (10-1/2" x 5" x 4-1/16") 1.8kg (4.0lbs) 266 x 138 x 103mm (10-1/2" x 5-7/16" x 4-1/16") Dimensions (L x W x H) 1.8kg (4.0lbs) \*Net weight Power supply cord 2.5m (8.2ft) 2.5m (8.2ft) Standard Equipment Depressed Centre Wheel, Lock Nut Wrench, Side grip ${}^{\star}\text{weight according to EPTA-Procedure 01/2003, including } \label{eq:weight according to EPTA-Procedure 01/2003, including } \\ \text{Wheel cover, Inner flange, Lock nut, Side grip; without Power supply cord}$

Items of standard equipment and specifications may vary by country or area.

### Makita Corporation